



Capacity lbs. (kg)	Pit Depth <sup>3,4</sup>	Overhead (OH <sup>3</sup> )
all	4'-6" (1370)	15'-0" (4570)

- ① Regular Bi-Parting Door.
- ② For extended sill or pass type, add 1.75" (44.5 mm) to Hoistway Depth for each door.
- ③ Designed for 8'-0" (2440) high cab & entrances.  
For 9'-0" (2745) high cab & entrances, Overhead + 1'-0" (305), Pit + 0'-6" (152)  
For 10'-0" (3050) high cab & entrances, Overhead + 2'-0" (610), Pit + 1'-0" (305)
- ④ For higher speed, contact us.

Speed fpm (m/s) <sup>4</sup>	Capacity lbs. (kg)	Hoistway		Platform		Size of Opening
		Width HW	Depth HD	Width PW	Depth PD	
25 to 150 (0.18 to 0.75)	5000	98"	128"	76"	120"	72"
	2250	2490	3250	1930	3050	1830
25 to 150 (0.18 to 0.75)	6000	98"	128"	76"	120"	72"
	2700	2490	3250	1930	3050	1830
25 to 100 (0.18 to 0.5)	8000	122"	128"	100"	120"	96"
	3600	3100	3250	2540	3050	2440
25 to 75 (0.18 to 0.38)	10000	122"	152"	100"	144"	96"
	4500	3100	3860	2540	3660	2440
25 to 75 (0.18 to 0.38)	12000	122"	176"	100"	168"	96"
	5450	3100	4470	2540	4270	2440

## Hydraulic "Holed" Freight Elevator CLASS A - Front Opening - Model A

Groupe manufacturier d'ascenseurs



Elevator Manufacturing Group