



Capacity lbs. (kg)	Pit Depth ³	Overhead (OH) ³
8000 (3600)	4'-6" (1370)	15'-0" 4570
10000 (4500)	5'-0" (1525)	
12000 (5450)	5'-0" (1525)	
15000 (6800)	5'-0" (1525)	
18000 (8150)	5'-6" (1675)	
20000 (9050)	5'-6" (1675)	
25000 (11350)	6'-0" (1830)	
30000 (13650)	6'-0" (1830)	

Speed fpm (m/s) ⁵	Capacity lbs. (kg)	Hoistway Width	Hoistway Depth	Platform Width	Platform Depth	Size of Opening
		HW	HD ²	PW	PD	
25 to 100 (0.18 to 0.5)	8000	122	128	100	120	96
	3600	3100	3250	2540	3050	2440
25 to 75 (0.18 to 0.38)	10000	122	152	100	144	96
	4500	3100	3860	2540	3660	2440
25 to 75 (0.18 to 0.38)	12000	122	176	100	168	96
	5450	3100	4470	2540	4270	2440
25 to 75 (0.18 to 0.38)	15000	157.5	200	124	192	120
	6800	4000	5080	3150	4880	3050
25 to 75 (0.18 to 0.38)	18000	157.5	224	124	216	120
	8150	4000	5690	3150	5490	3050
25 to 75 (0.18 to 0.38)	20000	181.5	248	148	240	144
	9050	4610	6300	3760	6100	3660
25 to 75 (0.18 to 0.38)	25000	181.5	248	148	240	144
	11350	4610	6300	3760	6100	3660
25 to 75 (0.18 to 0.38)	30000	181.5	248	148	240	144
	13650	4610	6300	3760	6100	3660

- ① Regular Bi-Parting Door.
- ② For Extended Sill or Pass Type, add 1,75" [44,5] to "HD" or "HDR" for each door.
- ③ Designed for 8'-0" [2440] high cab & entrances. For 9'-0" [2745] high Cab & entrances, Overhead + 1'-0" [305], Pit + 0'-6" [152]. For 10'-0" [3050] high Cab & entrances, Overhead + 2'-0" [610], Pit + 1'-0" [305]
- ④ Columns are to be extended from pit bottom to overhead beam supports. Where adequate brick or concrete walls are used, columns supports are not required. It is an understatement that sizes of structural columns and framing members are approximate. Accurate data will have to be provided by owner when exact loads, car sizes, floor heights etc., are available. All structural columns, ties connections are to be provided and erected by owner.
- ⑤ For C2 Loading Class, contact us.
- ⑥ For higher speed, contact us.

Hydraulic "Holed" Freight Elevator CLASS C - Front Opening - Without Column

Groupe manufacturier d'ascenseurs



Elevator Manufacturing Group