



FRONT & REAR OPENING

Capacity	Pit Depth <sup>3,4</sup>	Overhead (OH) <sup>3,5</sup>
all	4'-6" (1370)	15'-0" (4570)

- ① Regular Bi-Parting Door.
- ② For Extended Sill or Pass Type, add 1,75" [44,5] to "HD" or "HDR" for each door . Designed for 8'-0" [2440] high cab & entrances.
- ③ For 9'-0" [2745] high Cab & entrances, Overhead + 1'-0" [305], Pit + 0'-6" [152]. For 10'-0" [3050] high Cab & entrances, Overhead + 2'-0" [610], Pit + 1'-0" [305]
- ④ For higher speed, contact us.
- ⑤ For speed higher than 100 fpm [0,51], you must add to the overhead:  
Elevator speed 100 FPM [0,51] and under, 0 inch to the overhead  
Elevator speed Between 101 FPM [0,52] to 125 FPM [0,64], 2 inches to the overhead  
Elevator speed Between 126 FPM [0,64] to 150 FPM [0,75], 4 inches to the overhead  
Elevator speed over 150 FPM [0,75], contact us

Speed fpm (m/s) <sup>4</sup>	Capacity lbs. (kg)	Hoistway Width	Hoistway Depth	Platform Width	Platform Depth	Size of Opening
		HW	HD <sup>2</sup>	PW	PD	
25 to 150 (0.18 to 0.75)	5000	104	131	76	120	72
	2250	2640	3330	1930	3050	1830
	6000	104	131	76	120	72
	2700	2640	3330	1930	3050	1830
25 to 100 (0.18 to 0.5)	8000	128	155	100	144	96
	3600	3250	3330	2540	3050	2440
	10000	128	179	100	168	96
	4500	3250	4550	2540	4270	2440

## Hydraulic "Twin Jack Roped" Freight Elevator

CLASS A - Front & Rear Opening - Model A

Grpeur fabricant d'ascenseurs



Elevator Manufacturing Group