



FRONT & REAR OPENING

Capacity lbs. (kg)	Pit Depth ³	Overhead (OH ^{3,6})
8000 (3600)	5'-0" (1525)	15'-0" 4570
10000 (4500)	5'-0" (1525)	
12000 (5450)	5'-6" (1675)	
15000 (6800)	5'-6" (1675)	

- ① Regular Bi-Parting Door.
- ② For Extended Sill or Pass Type, add 1,75" [44,5] to "HD" or "HDR" for each door .
- ③ Designed for 8'-0" [2440] high cab & entrances.
For 9'-0" [2745] high Cab & entrances, Overhead + 1'-0" [305], Pit + 0'-6" [152]
For 10'-0" [3050] high Cab & entrances, Overhead + 2'-0" [610], Pit + 1'-0" [305]
- ④ Columns are to be extended from pit bottom to overhead beam supports. Where adequate brick or concrete walls are used, columns supports are not required. It is an understatement that sizes of structural columns and framing members are approximate. Accurate data will have to be provided by owner when exact loads, car sizes, floor heights etc., are available. All structural columns, ties connections are to be provided and erected by owner.
- ⑤ For higher speed, contact us.
- ⑥ For speed higher than 100 fpm [0.51] , you must add to the overhead:
Elevator speed 100 FPM [0,51] and under, 0 inch to the overhead
Elevator speed Between 101 FPM [0,52] to 125 FPM [0,64], 2 inches to the overhead
Elevator speed Between 126 FPM [0,64] to 150 FPM [0,75], 4 inches to the overhead
Elevator speed over 150 FPM [0,75], contact us
- ⑦ For C2 Loading Class, contact us

Speed fpm (m/s) ⁵	Capacity lbs. (kg)	Hoistway Width	Hoistway Depth	Platform Width	Platform Depth	Size of Opening
		HW	HD ²	PW	PD	
25 to 100 (0.18 to 0.5)	8000	130	131	100	120	96
	3600	3300	3330	2540	3050	2440
25 to 75 (0.18 to 0.38)	10000	130	155	100	144	96
	4500	3300	3940	2540	3660	2440
	12000	130	179	100	168	96
	5450	3300	4550	2540	4270	2440
	15000	160	203	124	192	120
6800	4065	5160	3150	4880	3050	

Hydraulic "Twin Jack Roped" Freight Elevator CLASS C - Front & Rear Opening - Without Column

Groupe manufacturier d'ascenseurs



Elevator Manufacturing Group