



Capacity lbs. (kg)	Pit Depth ^{3,4}	Overhead (OH ³)
all	4'-6" (1370)	15'-0" (4570)

- ① Regular Bi-Parting Door.
- ② For extended sill or pass type, add 1.75" (44.5 mm) to Hoistway Depth for each door.
- ③ Designed for 8'-0" (2440) high cab & entrances.
For 9'-0" (2745) high cab & entrances, Overhead + 1'-0" (305), Pit + 0'-6" (152)
For 10'-0" (3050) high cab & entrances, Overhead + 2'-0" (610), Pit + 1'-0" (305)
- ④ For higher speed, contact us.

Speed fpm (m/s) ⁴	Capacity lbs. (kg)	Hoistway Width	Hoistway Depth	Platform Width	Platform Depth	Size of Opening
		HW	HD	PW	PD	
25 to 150 (0.18 to 0.75)	5000 2250	122" 3100	152" 3860	100" 2540	144" 3660	96" 2440
25 to 150 (0.18 to 0.75)	6000 2700	122" 3100	152" 3860	100" 2540	144" 3660	96" 2440
25 to 100 (0.18 to 0.5)	8000 3600	146" 3710	152" 3860	124" 3150	144" 3660	120" 3050
25 to 75 (0.18 to 0.38)	10000 4500	146" 3710	176" 4470	124" 3150	168" 4270	120" 3050
25 to 75 (0.18 to 0.38)	12000 5450	170" 4320	200" 5080	148" 3760	192" 4780	144" 3660

Hydraulic "Holed" Freight Elevator CLASS A - Front Opening - Model B

Groupe manufacturier d'ascenseurs



Elevator Manufacturing Group