



FRONT & REAR OPENING

Capacity lbs. (kg)	Pit Depth ^{3,4}	Overhead (OH ³)
all	4'-6" (1370)	15'-0" (4570)

- ① Regular Bi-Parting Door.
- ② For extended sill or pass type, add 1.75" (44.5 mm) to Hoistway Depth for each door.
- ③ Designed for 8'-0" (2440) high cab & entrances.
For 9'-0" (2745) high cab & entrances, Overhead + 1'-0" (305), Pit + 0'-6" (152)
For 10'-0" (3050) high cab & entrances, Overhead + 2'-0" (610), Pit + 1'-0" (305)
- ④ For higher speed, contact us.

Speed fpm (m/s) ⁴	Capacity lbs. (kg)	Hoistway Width	Hoistway Depth	Platform Width	Platform Depth	Size of Opening
		HW	HD ²	PW	PD	
25 to 150 (0.18 to 0.75)	5000	122"	155"	100"	144"	96"
	2250	3100	3940	2540	3660	2440
25 to 150 (0.18 to 0.75)	6000	122"	155"	100"	144"	96"
	2700	3100	3940	2540	3660	2440
25 to 100 (0.18 to 0.5)	8000	146"	155"	124"	144"	120"
	3600	3710	3940	3150	3660	3050
25 to 75 (0.18 to 0.38)	10000	146"	179"	124"	168"	120"
	4500	3710	4550	3150	4270	3050
25 to 75 (0.18 to 0.38)	12000	170"	203"	148"	192"	144"
	5450	4320	5160	3760	4780	3660

Hydraulic "Holed" Freight Elevator CLASS A - Front & Rear Opening - Model B

Groupe manufacturier d'ascenseurs



Elevator Manufacturing Group