



Capacity lbs. (kg)	Max. Travel <sup>3,5</sup>	Pit Depth <sup>3,4</sup>	Overhead (OH <sup>3,5</sup> )
5000 (2250)	14'-6" (4420)	4'-6" (1370)	15'-6" (4725)
6000 (2700)	14'-6" (4420)		
8000 (3600)	14'-6" (4420)		
10000 (4500)	14'-0" (4270)		
12000 (5450)	14'-0" (4270)		

- ① Regular Bi-Parting Door.
- ② For Extended Sill or Pass Type, add 1,75" [44,5] to "HD" or "HDR" for each door.
- ③ Designed for 8'-0" [2440] high cab & entrances.  
For 9'-0" [2745] high Cab & entrances, Overhead + 0'-6" [152], Pit + 0'-6" [152], min travel will be increase by 1'-0".  
For 10'-0" [3050] high Cab & entrances, Overhead + 1'-0" [305], Pit + 1'-0" [305], min travel will be increase by 2'-0".
- ④ For higher speed, contact us.
- ⑤ For every inch added on the travel (floor to floor), you must add the same either to the ⑥ pit or to the overhead.

Speed fpm (m/s) <sup>4</sup>	Capacity lbs. (kg)	Hoistway Width	Hoistway Depth	Platform Width	Platform Depth	Size of Opening
		HW	HD <sup>2</sup>	PW	PD	
25 to 150 (0.18 to 0.75)	5000	124	152	100	144	96
	2250	3150	3860	2540	3660	2440
	6000	124	152	100	144	96
	2700	3150	3860	2540	3660	2440
25 to 75 (0.18 to 0.38)	8000	150	152	124	144	120
	3600	3810	3860	3150	3660	3050
	10000	150	176	124	168	120
	4500	3810	4470	3150	4270	3050
	12000	174	200	148	192	144
	5450	4420	5080	3760	4880	3660

## Hydraulic "Twin Jack Direct" Freight Elevator CLASS A - Front Opening - Model B

Grpeur fabricant d'ascenseurs



Elevator Manufacturing Group