



FRONT & REAR OPENING

Capacity lbs. (kg)	Max. Travel <sup>3,5</sup>	Pit Depth <sup>3,4</sup>	Overhead (OH) <sup>3,5</sup>
5000 (2250)	14'-6" (4420)		
6000 (2700)	14'-6" (4420)		
8000 (3600)	14'-6" (4420)	4'-6" (1370)	15'-6" (4725)
10000 (4500)	14'-0" (4270)		
12000 (5450)	14'-0" (4270)		

- ① Regular Bi-Parting Door.
- ② For Extended Sill or Pass Type, add 1,75" [44,5] to "HD" or "HDR" for each door.
- ③ Designed for 8'-0" [2440] high cab & entrances.  
For 9'-0" [2745] high Cab & entrances, Overhead + 0'-6" [152], Pit + 0'-6" [152], min travel will be increase by 1'-0".  
For 10'-0" [3050] high Cab & entrances, Overhead + 1'-0" [305], Pit + 1'-0" [305], min travel will be increase by 2'-0".
- ④ For higher speed, contact us.
- ⑤ For every inch added on the travel (floor to floor), you must add the same either to the pit or to the overhead.
- ⑥ pit or to the overhead.

Speed fpm (m/s) <sup>4</sup>	Capacity lbs. (kg)	Hoistway Width	Hoistway Depth	Platform Width	Platform Depth	Size of Opening
		HW	HD <sup>2</sup>	PW	PD	
25 to 150 (0.18 to 0.75)	5000	100	131	76	120	72
	2250	2540	3330	1930	3050	1830
	6000	100	131	76	120	72
	2700	2540	3330	1930	3050	1830
25 to 75 (0.18 to 0.38)	8000	124	131	100	120	96
	3600	3150	3330	2540	3050	2440
	10000	126	155	100	144	96
	4500	3200	3940	2540	3660	2440
	12000	126	179	100	168	96
	5450	3200	4550	2540	4270	2440

## Hydraulic "Twin Jack Direct" Freight Elevator CLASS A - Front & Rear Opening - Model A

Grpeur fabricant d'ascenseurs



Elevator Manufacturing Group