



Capacity lbs. (kg)	Max. Travel	Pit Depth ^{3,4}	Overhead (OH ³)	Cab height
8000 (4500)	14'-6" (4420)	4'-6" (1370)	15'-6" (4725)	8'-0" (2440)
15000 (6800)	16'-6" (5030)	5'-6" (1675)	17'-0" (5180)	10'-0" (3050)

- ① Regular Bi-Parting Door.
- ② For Extended Sill or Pass Type, add 1,75" [44,5] to 'HD' or 'HDR' for each door.
- ③ Columns are to be extended from pit bottom to overhead beam supports. Where adequate brick or concrete walls are used, columns supports are not required. It is an understatement that sizes of structural columns and framing members are approximate. Accurate data will have to be provided by owner when exact loads, car sizes, floor heights etc., are available. All structural columns, ties connections are to be provided and erected by owner.
- ④ For every inch added on the travel (floor to floor), you must add the same either to the pit or to the overhead.
- ⑤ For higher speed, contact

Hydraulic "Twin Jack Direct" Freight Elevator CLASS B - Front Opening - Model B

Speed fpm (m/s) ⁴	Capacity lbs. (kg)	Hoistway Width	Hoistway Depth	Platform Width	Platform Depth	Size of Opening
		HW	HD ²	PW	PD	
25 to 100 (0.18 to 0.5)	8000	124	248	124	240	120
	4500	3150	6300	3150	6100	
25 to 75 (0.18 to 0.38)	15000	148	308	148	300	144
	6800	3760	7825	3760	7620	

Groupe manufacturier d'ascenseurs



Elevator Manufacturing Group