



FRONT & REAR OPENING

Capacity lbs. (kg)	Max. Travel	Pit Depth 3,4	Overhead (OH ³)	Cab height
8000 (4500)	14'-6" (4420)	4'-6" (1370)	15'-6" (4725)	8'-0" (2440)
15000 (6800)	16'-6" (5030)	5'-6" (1675)	17'-0" (5180)	10'-0" (3050)

- ① Regular Bi-Parting Door.
- ② For Extended Sill or Pass Type, add 1,75" [44,5] to 'HD' or 'HDR' for each door.
- ③ Columns are to be extended from pit bottom to overhead beam supports. Where adequate brick or concrete walls are used, columns supports are not required. It is an understatement that sizes of structural columns and framing members are approximate. Accurate data will have to be provided by owner when exact loads, car sizes, floor heights etc., are available. All structural columns, ties connections are to be provided and erected by owner.
- ④ For every inch added on the travel (floor to floor), you must add the same either to the pit or to the overhead.
- ⑤ For higher speed, contact

Hydraulic "Twin Jack Direct" Freight Elevator CLASS B - Front & Rear Opening - Model A

Speed fpm (m/s) ⁴	Capacity lbs. (kg)	Hoistway Width	Hoistway Depth	Platform Width	Platform Depth	Size of Opening
		HW	HD ²	PW	PD	
25 to 100 (0.18 to 0.5)	8000 3600	126 3200	251 6375	100 2540	240 6100	96 2440
25 to 75 (0.18 to 0.38)	15000 6800	150 3810	311 7900	124 3150	300 7620	120 3050

Grande manufacture d'ascenseurs



Elevator Manufacturing Group