



Capacity	Pit Depth <sup>3,4</sup>	Overhead (OH) <sup>3,5</sup>
all	4'-6" (1370)	15'-0" (4570)

- ① Regular Bi-Parting Door.
- ② For Extended Sill or Pass Type, add 1,75" [44,5] to "HD" or "HDR" for each door. Designed for 8'-0" [2440] high cab & entrances.
- ③ For 9'-0" [2745] high Cab & entrances, Overhead + 1'-0" [305], Pit + 0'-6" [152]. For 10'-0" [3050] high Cab & entrances, Overhead + 2'-0" [610], Pit + 1'-0" [305].
- ④ For higher speed, contact us.
- ⑤ For speed higher than 100 fpm [0,51], you must add to the overhead:  
Elevator speed 100 FPM [0,51] and under, 0 inch to the overhead  
Elevator speed Between 101 FPM [0,52] to 125 FPM [0,64], 2 inches to the overhead  
Elevator speed Between 126 FPM [0,64] to 150 FPM [0,75], 4 inches to the overhead  
Elevator speed over 150 FPM [0,75], contact us

Speed fpm (m/s) <sup>4</sup>	Capacity lbs. (kg)	Hoistway Width	Hoistway Depth	Platform Width	Platform Depth	Size of Opening
		HW	HD <sup>2</sup>	PW	PD	
25 to 150 (0.18 to 0.75)	5000	104	128	76	120	72
	2250	2640	3250	1930	3050	1830
	6000	104	128	76	120	72
25 to 100 (0.18 to 0.5)	2700	2640	3250	1930	3050	1830
	8000	128	128	100	120	96
	3600	3250	3250	2540	3050	2440
25 to 100 (0.18 to 0.5)	10000	128	152	100	144	96
	4500	3250	3860	2540	3660	2440
	12000	128	176	100	168	96
	5450	3250	4470	2540	4270	2440

## Hydraulic "Twin Jack Roped" Freight Elevator CLASS A - Front Opening - Model A

Groupe manufacturier d'ascenseurs



Elevator Manufacturing Group