



Capacity	Pit Depth ^{3,4}	Overhead (OH) ^{3,5}
all	4'-6" (1370)	15'-0" (4570)

- ① Regular Bi-Parting Door.
- ② For Extended Sill or Pass Type, add 1,75" [44,5] to "HD" or "HDR" for each door . Designed for 8'-0" [2440] high cab & entrances.
- ③ For 9'-0" [2745] high Cab & entrances, Overhead + 1'-0" [305], Pit + 0'-6" [152]. For 10'-0" [3050] high Cab & entrances, Overhead + 2'-0" [610], Pit + 1'-0" [305]
- ④ For higher speed, contact us.
- ⑤ For speed higher than 100 fpm [0,51] , you must add to the overhead:
 Elevator speed 100 FPM [0,51] and under, 0 inch to the overhead
 Elevator speed Between 101 FPM [0,52] to 125 FPM [0,64], 2 inches to the overhead
 Elevator speed Between 126 FPM [0,64] to 150 FPM [0,75], 4 inches to the overhead
 Elevator speed over 150 FPM [0,75], contact us

Speed fpm (m/s) ⁴	Capacity lbs. (kg)	Hoistway Width	Hoistway Depth	Platform Width	Platform Depth	Size of Opening
		HW	HD ²	PW	PD	
25 to 150 (0.18 to 0.75)	5000	128	152	100	144	96
	2250	3250	3860	2540	3660	2440
	6000	128	152	100	144	96
	2700	3250	3860	2540	3660	2440
25 to 100 (0.18 to 0.5)	8000	152	152	124	144	120
	3600	3860	3860	3150	3660	3050
	10000	152	176	124	168	120
	4500	3860	4470	3150	4270	3050
	12000	176	200	148	192	144
	5450	4470	5080	3760	4780	3660

Hydraulic "Twin Jack Roped" Freight Elevator CLASS A - Front Opening - Model B

Groupe manufacturier d'ascenseurs



Elevator Manufacturing Group