



Capacity	Pit Depth ^{3,4}	Overhead (OH) ^{3,5}
all	4'-6" (1370)	15'-0" (4570)

- ① Regular Bi-Parting Door.
- ② For Extended Sill or Pass Type, add 1,75" [44,5] to "HD" or "HDR" for each door. Designed for 8'-0" [2440] high cab & entrances.
- ③ For 9'-0" [2745] high Cab & entrances, Overhead + 1'-0" [305], Pit + 0'-6" [152]. For 10'-0" [3050] high Cab & entrances, Overhead + 2'-0" [610], Pit + 1'-0" [305]
- ④ For higher speed, contact us.
- ⑤ For speed higher than 100 fpm [0,51], you must add to the overhead:
Elevator speed 100 FPM [0,51] and under, 0 inch to the overhead
Elevator speed Between 101 FPM [0,52] to 125 FPM [0,64], 2 inches to the overhead
Elevator speed Between 126 FPM [0,64] to 150 FPM [0,75], 4 inches to the overhead
Elevator speed over 150 FPM [0,75], contact us

Speed fpm (m/s) ⁴	Capacity lbs. (kg)	Hoistway Width	Hoistway Depth	Platform Width	Platform Depth	Size of Opening
		HW	HD ²	PW	PD	
25 to 150 (0.18 to 0.75)	6000	128	155	100	144	96
	2700	3250	3940	2540	3660	2440
	8000 3600	152 3860	155 3940	124 3150	144 3660	120 3050
25 to 100 (0.18 to 0.5)	10000	152	179	124	168	120
	4500	3860	4550	3150	4270	3050
	12000 5450	176 4470	203 5160	148 3760	192 4780	144 3660

Hydraulic "Twin Jack Roped" Freight Elevator CLASS A - Front & Rear Opening - Model B

Groupe manufacturier d'ascenseurs



Elevator Manufacturing Group