



Capacity lbs. (kg)	Pit Depth	Overhead (OH ⁵)	Cab Height
8000 (4500)	5'-0" (1525)	15'-0" (4570)	8'-0" (2440)
15000 (6800)	5'-6" (1675)	17'-0" (5180)	10'-0" (3050)

- ① Regular Bi-Parting Door.
- ② For Extended Sill or Pass Type, add 1,75" [44,5] to "HD" or "HDR" for each door.
- ③ Columns are to be extended from pit bottom to overhead beam supports. Where adequate brick or concrete walls are used, columns supports are not required. It is an understatement that sizes of structural columns and framing members are approximate. Accurate data will have to be provided by owner when exact loads, car sizes, floor heights etc., are available. All structural columns, ties connections are to be provided and erected by owner.
- ④ For higher speed, contact us.
- ⑤ For speed higher than 100 fpm [0.51] , you must add to the overhead:
Elevator speed 100 FPM [0,51] and under, 0 inch to the overhead
Elevator speed Between 101 FPM [0,52] to 125 FPM [0,64], 2 inches to the overhead
Elevator speed Between 126 FPM [0,64] to 150 FPM [0,75], 4 inches to the overhead
Elevator speed over 150 FPM [0,75], contact us
- ⑥ For maximum travel contact us

Hydraulic "Twin Jack Roped" Freight Elevator CLASS B - Front Opening - Model A

Speed fpm (m/s) ⁴	Capacity lbs. (kg)	Hoistway Width	Hoistway Depth	Platform Width	Platform Depth	Size of Opening
		HW	HD ²	PW	PD	
25 to 100 (0.18 to 0.5)	8000	128	248	100	240	96
	4500	3250	6300	2540	6100	2440
25 to 75 (0.18 to 0.38)	15000	157.5	308	124	300	120
	6800	4000	7825	3150	7620	3050

Grande manufacture d'ascenseurs



Elevator Manufacturing Group