



Capacity lbs. (kg)	Max. Travel ^{3,5}	Pit Depth ^{3,4}	Overhead (OH ^{3,5})
5000 (2250)	14'-6" (4420)		
6000 (2700)	14'-6" (4420)		
8000 (3600)	14'-6" (4420)	4'-6" (1370)	15'-6" (4725)
10000 (4500)	14'-0" (4270)		
12000 (5450)	14'-0" (4270)		

- ① Regular Bi-Parting Door.
- ② For Extended Sill or Pass Type, add 1,75" [44,5] to "HD" or "HDR" for each door.
- ③ Designed for 8'-0" [2440] high cab & entrances.
For 9'-0" [2745] high Cab & entrances, Overhead + 0'-6" [152], Pit + 0'-6" [152], min travel will be increase by 1'-0".
For 10'-0" [3050] high Cab & entrances, Overhead + 1'-0" [305], Pit + 1'-0" [305], min travel will be increase by 2'-0".
- ④ For higher speed, contact us.
- ⑤ For every inch added on the travel (floor to floor), you must add the same either to the
- ⑥ pit or to the overhead.

Speed fpm (m/s) ⁴	Capacity lbs. (kg)	Hoistway Width	Hoistway Depth	Platform Width	Platform Depth	Size of Opening
		HW	HD ²	PW	PD	
25 to 150 (0.18 to 0.75)	5000	124	155	100	144	96
	2250	3150	3940	2540	3660	2440
	6000	124	155	100	144	96
	2700	3150	3940	2540	3660	2440
25 to 75 (0.18 to 0.38)	8000	150	155	124	144	120
	3600	3810	3940	3150	3660	3050
	10000	150	179	124	168	120
	4500	3810	4550	3150	4270	3050
	12000	174	203	148	192	144
	5450	4420	5160	3760	4880	3660

Hydraulic "Twin Jack Direct" Freight Elevator CLASS A - Front & Rear Opening - Model B

Groupe manufacturier d'ascenseurs



Elevator Manufacturing Group